

PRODUCT DESCRIPTION

Petrowrap Pluslite Mastic is an integral component of the Petrowrap Petrolatum System. Petrowrap Pluslite Mastic is based upon reinforced petrolatum compound, blended with thermal extenders, inert fillers, corrosion inhibitors and wide spectrum biocide.

PRODUCT CHARACTERISTICS

Petrowrap Pluslite Mastic is formulated for stability and plasticity over a wide temperature range. Petrowrap Pluslite Mastic will profile crevices and sharp angular profile changes enabling Petrowrap Petrolatum Tape to be applied without bridging or voiding.

PRODUCT USES

Pipeline: Above ground, below ground, and submerged pipe and fittings.

Other: Joint sealing, joint reinstatement, temporary leak repair damaged drums / containers.

PRODUCT PROPERTIES

Property	Test Method	Value
Specific Gravity	ASTM D70 @25°C (Mod)	0.61 (average)
Drop Melting Point	ASTM D127 (Mod)	65°C
Volume per Block*		0.003m ³
Application Temperature	-10 to +50°C	
Service Temperature	-10 to +55°C	
Service Life	30 years +	
Shelf Life	30 years +	

- Note that the QTY of mastic required is applicator dependent. Confirmatory trials should be concluded where possible to determine requirements.

AVAILABLE PACK SIZES

3L	Block	Carton	QTY/8
20L	Tub	Carton	QTY/1



EPDM GASKET JOINTS

Prior to Petrowrap 4 step application.

Apply 2 wraps of Petrowrap Overwrap tape directly on cleaned joint to protect EPDM gasket integrity

Disclaimer

All Statements/data presented herein are given in good faith and believed to be appropriate and reliable. However it is given without express or implied warrant or guarantees. Potential users of our materials are urged to conduct confirmatory trials to satisfy themselves as to the suitability of the selected product for their particular end use prior to purchase.