

PRODUCT DESCRIPTION

Petrowrap Petrolatum Primer is an integral component of the Petrowrap Petrolatum System. Petrowrap Petrolatum Primer is a petrolatum compound, blended with inert fillers, corrosion inhibitors and wide spectrum biocide.

PRODUCT CHARACTERISTICS

Petrowrap Petrolatum Primer is manufactured in accordance with AWWA Standard C217-04. Petrowrap Petrolatum Primer is formulated for stability and plasticity over a wide temperature range. Petrowrap Petrolatum Primer will profile minor surface imperfections and enable uniform adhesion of Petrowrap Petrolatum Mastic and Petrowrap Petrolatum Tape to the cleaned substrate.

PRODUCT USES

Pipeline: Above ground, below ground, and submerged pipe and fittings. Other: Tie rods, starter bars, bond breaker, slipform release tape, roof sheet isolation tape.

PRODUCT PROPERTIES

Property	Test Method	Value
Flash Point	ASTM D92	180°C
Specific Gravity	ASTM D70 @25° C (Mod)	1.1 (Average)
Drop Melting Point	ASTM D127 (Mod)	55° (Average)
Cone Penetration at 25°C, 100g wt.5 sec.,; mm	ASTM D937 (Mod)	15mm (Average)
Coverage		5m ² /kg (Average)
Application Temperature	-10 to +50°C	
Service Temperature	-10 to +75°C	
Service Life	30 years +	
Shelf Life	30 years +	

AVAILABLE PACK SIZES

1L	Tub	Carton	QTY/12
4L	Tub	Carton	QTY/4

EPDM GASKET JOINTS

Prior to Petrowrap 4 step application.
Apply 2 wraps of Petrowrap Overwrap tape directly on cleaned joint to protect EPDM gasket integrity



Disclaimer

All Statements/data presented herein are given in good faith and believed to be appropriate and reliable. However it is given without express or implied warrant or guarantees. Potential users of our materials are urged to conduct confirmatory trials to satisfy themselves as to the suitability of the selected product for their particular end use prior to purchase.